



L.R. Nelson Corporation
One Sprinkler Lane
Peoria, Illinois 61615

Title:

**Official Tennis Court Layout
 (Double Court)**

7500 ADV with or without model 6101 Sod Cup
 60 PSI Operating Pressure at Sprinkler Head, 30 G.P.M. Water Supply

Scale: **1"=20'0"**

File: TNSD7560.DWG

This design is for reference only. Your actual field dimensions may vary.
 Please adjust design as necessary.

Notes:

1. Minimum lateral pipe size downstream of valve and before first sprinkler will be 2" in size.
2. Lateral piping to second sprinkler and beyond could remain 2" in size or can be reduced to match flow at that segment.
3. Lateral piping layout is prepared for installation via vibratory plow or trenching.
4. Mainline and valve location may change depending upon overall sports complex layout.
5. Mainline size will vary depending upon overall sports complex layout.
6. Thrust blocking at mainline and valve locations required.

Key



Nelson 7500 ADV (Pop-Up Rotor)

Part Circle Usage
 Quarter Circle – 14.4 G.P.M. # 5 Nozzle
 Half Circle – 14.4 G.P.M. # 5 Nozzle



Nelson 1 1/2" Electric Valve

(Use Globe Configuration)



Nelson 7645 1" Quick Coupling Valve



**Mainline Piping
 PVC Class 200 SDR 21**
 (number indicates size)



Lateral Piping PVC Class 200
 (number indicates size)

L.R. NELSON MATERIAL QUANTITIES

- 8 - L.R. Nelson 7500 ADV Quarter Circle Rotors
- 4 - L.R. Nelson 7500 ADV Half Circle Rotors
- 6 - L.R. Nelson 1 1/2" Electric Valves
- 2 - L.R. Nelson 7645 1" Quick Coupling Valves
- 1 - L.R. Nelson SmartZone Controller
- 8520 or 8536 with (0) Plus4 Modules

Notes

