NEW OPTIONS FOR WT & M SERIES TRANSFORMERS

TIMER-READY (-TR) OR X10 REMOTE CONTROL (-X10)

SPECIFICATIONS:

FOR WT SERIES:

- 1/8" Extruded Aluminum Enclosure Powder Coated Black Polyester w/Lockable Cover (Raintight Nema 3R) Above Grade.
- High Temperature Class "B" 130°C Magnetic Transformer, Isolation Type
- 120 Primary, 12.5 Volt Secondary, 50/60 Hertz/Cycle
- 6' (18/3) SJT-WA Weatherproof Grounded Power Cord (120v)
- On/Off Control Via Rocker Switch
- Heavy Duty (75 Amp) Terminal Block Easily Handles Extra Sets of Cable
- Resetable Circuit Breakers for Overload or Short Circuit Protection
- UL 1838 Listed. The Only U.S. Standard for Low-Voltage Landscape Lighting Systems.

FOR M SERIES:

• Same as Above Except: The Enclosure is Stainless Steel (18 Guage w/Hinged Locking Door). 1/2" Knock-Outs for Conduit Feed. Upgrade Accessories for Field Installations. Does Not Require Factory Installations of all Accessories.

FEATURES:

- Timer-Ready Receptacle for Use with Plug-In Timer (Intermatic)
- Simply Plug In Timer for Use or X10 Module for Remote Control
- Easy Replacement of Timer or Control Device (seconds)
- Manual Operation
- 3/4" and 1" Knockouts Available. Consult Factory.

CATALOG

ALL WT & M SERIES TRANSFORMERS

WT-12-100-TR	MST-12-200-TR
WT-12-200-TR	MST-12-300-TR
WT-212-200-TR	MST-212-300-TR
WT-12-300-TR	MST-212-600-TR
WT-212-300-TR	MLT-312-900-TR
WT-212-600-TR	MLT-412-1200-TR
WT-312-900-TR	
WT-412-1200-TR	

OTHER OPTIONS:

- -D Dimmer
- -PC Attached Photo Cell
- -RPC Remote Photo Cell w/15-50 foot Cord
- -MV Multi-Voltage Output 3 Taps (12.5, 13.5, 14.5 v)





25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630 (949) 830-1350 = FAX (949) 830-3390

sales@focusindustries.com www.focusindustries.com MEMBER OF



MST-212-600-X10

6″